PRODUCT DATASHEET

Racks, Cabinets & Power

Wall-Mount Network Cabinets

4U · 6U · 12U · 15U · 19-inch

4U · 6U · 12U (600 × 450 MM) · 15U (600 × 600 MM) · TEMPERED GLASS DOOR

iSHCO wall-mount network cabinets house switches, patch panels and small servers in offices, shops and floor distribution points. Available in **4U, 6U, 12U and 15U** with a lockable tempered-glass front door.

Cabinets are built from cold-rolled steel with a black powder-coat finish, top ventilation slots with fan cut-outs, side vents and removable side panels. 4U–12U cabinets are 600 mm wide × 450 mm deep; the 15U cabinet is 600 × 600 mm.

19-inch | Glass door | Lockable | Wall-mount | SPCC Steel

Features & Benefits

01

- Standard 19-inch mounting, adjustable front rack rails
- Removable side panels for easy access and installation
- Cable entry knock-outs on top and bottom
- Wall-mount keyhole slots on rear panel, supplied with wall plugs
- Fully assembled – ready to mount
- Lockable tempered-glass front door with key lock, reversible hinge
- Top ventilation with cut-outs for up to 2 cooling fans
- Cold-rolled SPCC steel 1.2 mm frame, black powder coat (RAL 9004)
- Static load capacity up to 60 kg
- Ground stud for cabinet earthing

WEBSITE
www.ishco.uk

EMAIL
info@ishco.uk

PHONE
+964 07501144051 · +964 07501144052

LOCATION
Erbil, Sultan Muthafar

SCAN TO VISIT

Wall-Mount Network Cabinets

RACKS, CABINETS & POWER

Specifications | Ordering Guide

Technical Specifications

02

Parameter	Specification
Rack units	4U · 6U · 12U · 15U
Width × depth	600 × 450 mm (4U–12U) · 600 × 600 mm (15U)
Height	4U: 280 mm · 6U: 370 mm · 12U: 635 mm · 15U: 770 mm
Mounting standard	19-inch, IEC 60297 / EIA-310
Front door	Tempered glass 4 mm, steel frame, key lock
Side panels	Removable, ventilated
Material	SPCC cold-rolled steel 1.2 mm
Finish	Black powder coat, RAL 9004
Static load	60 kg
Ventilation	Top fan cut-outs (2), side vents
Cable entry	Top and bottom knock-outs
Protection	IP20
Delivery	Fully assembled

Ordering Information

03

Part No.	Description	W × D × H (mm)	Load
ISH-WC-4U-6045	4U wall-mount cabinet, glass door	600 × 450 × 280	60 kg
ISH-WC-6U-6045	6U wall-mount cabinet, glass door	600 × 450 × 370	60 kg
ISH-WC-12U-6045	12U wall-mount cabinet, glass door	600 × 450 × 635	60 kg
ISH-WC-15U-6060	15U wall-mount cabinet, glass door	600 × 600 × 770	60 kg

APPLICATIONS

- Office and SME network equipment
- Floor distributors and IDF closets
- CCTV / NVR and access-control installations
- Retail, hospitality and education sites

STANDARDS & COMPLIANCE

- IEC 60297-3-100 / EIA-310-D
- DIN 41494
- IP20 (IEC 60529)
- RoHS

PACKAGE CONTENTS

- 1 × assembled cabinet with key lock (2 keys)
- Cage nuts and screws (M6)
- Wall mounting plugs and screws
- Ground wire

Note: Specifications are typical values and may be improved without notice. For custom lengths, colours, quantities or OEM requirements please contact the iSHCO team using the details below.

WEBSITE
www.ishco.uk

EMAIL
info@ishco.uk

PHONE
+964 07501144051 · +964 07501144052

LOCATION
Erbil, Sultan Muthafar

SCAN TO VISIT