



Cat6A S/FTP Shielded Patch Cord (RJ45 to RJ45)

پاچ کۆردی Cat6A S/FTP شیلددار (RJ45 بۆ RJ45)
سلك توصيل Cat6A S/FTP مدّرع (RJ45 إلی RJ45)

ISH-P108

ISHCO

OVERVIEW

Cat6A S/FTP shielded patch cord for 10GBASE-T networks — braid and foil screening, 100% copper and shielded gold-plated RJ45 plugs. Available in several lengths.

پاچ کۆردی Cat6A S/FTP شیلددار بۆ تۆری 10GBASE-T — شیلدی برهید و فویل، مسی ۱۰۰٪ و کۆنیکتهری RJ45 ی زیرکاری. به چەند درێژیهک بهردهسته.

سلك توصيل Cat6A S/FTP مدّرع لشیكات 10GBASE-T — تدریع ضفیره ورقائق، نحاس ۱۰۰٪ وقوابس RJ45 مدّرعة مطلیة بالذهب. متوفر بعده أطوال.



KEY FEATURES

- Cat6A / Class EA — 500 MHz, 10GBASE-T ready
- S/FTP double screening against alien crosstalk
- Shielded metal RJ45 plugs, gold-plated
- 100% copper conductors
- LSZH jacket

SPECIFICATIONS

Category	Cat6A / Class EA (ANSI/TIA-568.2-D, ISO/IEC 11801)
Conductor	26 AWG stranded bare copper, 4 pairs
Shielding	S/FTP (braid + foil per pair)
Bandwidth	500 MHz
Data rate	10 Gbps (10GBASE-T up to 100 m channel)
Connector	Shielded RJ45 8P8C, gold-plated 50μ"
Length	On request (0.5 – 5 m)
Jacket	LSZH, OD ≈ 6.2 mm
Operating temperature	–20 °C to +60 °C